

Prayon s.a.

EXTRACTION OF URANIUM FROM  
PHOSPHORIC ACID

THE GOOD PRACTICE

---

Presented by Alain GERMEAU, Head of Research Department



## Stake in term of Resources

### Uranium Resources (in $10^3$ tons U)

- In 2003, classical resources known :

< 130 USD/Kg U	:	4588
< 80 USD/Kg U	:	3537
< 40 USD/Kg U	:	2523
  
  - Resources contained in phosphates :

< 130 USD/Kg U	:	22000
----------------	---	-------
  
  - Resources contained in Moroccan phosphates :

< 120 USD/Kg U	:	6500
----------------	---	------
-



# To invest nowadays in Uranium extraction from phosphoric acid

## 1. STAKE IN TERM OF ECONOMY

**In 1980** : PRAYON invests in the following economic environment :

SPOT PRICE NUEXCO :	42 US\$/lb $U_3O_8$	=	109 US\$/kg U
SALES PRICE :	3400 FB/kg $U_3O_8$	=	137 US\$/kg U
COMPLETE COST PRICE :	2800 FB/kg U	=	96 US\$/kg U

**In 1998** : PRAYON stops this activity in the following economic environment:

SPOT PRICE NUEXCO :	10 US\$/lb $U_3O_8$	=	26 US\$/kg U
SALES PRICE :	1200 FB/kg $U_3O_8$	=	39 US\$/kg U
COMPLETE COST PRICE :	2590 FB/kg U	=	71 US\$/kg U

---



# To invest nowadays in Uranium extraction from phosphoric acid

## 2. ACTUAL SITUATION

Spot price NUEXCO : 40.5 US\$/lb  $U_3O_8$  = 105 US\$/kg U

A long term sales contract could be concluded at 65 US\$/lb  $U_3O_8$  = 168 US\$/kg U


A unit of recovery of the uranium from phosphoric acid, with an annual capacity of minimum 100 tons of U and a 20 years amortization, will show a cost price that may vary from 75 and 130 US\$/kg U

This cost price will depend on :

- \* the U and organic matter content in the natural phosphate
- \* the local economic environment



## Spot Price Evolution of NUEXCO





## Historical Background

- In the Fifties : First industrial realizations with solvent extraction of Uranium in Florida
- End of the Sixties : Elaboration of a range of solvents made out of neutral or acidic esters of phosphoric acid by a team of the National Oak Ridge Laboratory (USA)
- Birth of a range of processes named according to the solvent used
- Building of plants using one process or another, in the USA, in Belgium, In Canada, in Iraq and in Taiwan.
  - First operational one : Grace's Plant in Bartow, Florida (1976)
  - Last to stop its activities : Prayon Plant in Engis, Belgium (1998)



## Historical Background

- DEHPA/TOPO appeared to be the most efficient process and plants converted to it.
- DEHPA/TOPO system revealed itself as the best one thanks to its great stability and very good selectivity.
- Despite works performed with new solvents, DEHPA/TOPO process in its latest evolutions remains THE REFERENCE PROCESS



## Prayon and the uranium extraction from phosphoric acid

- **End of the Seventies** : Prayon and Union Minière shared their expertise to develop the industrial application of the DEHPA/TOPO Process for uranium-bearing Moroccan acid.
- Based on pilot test results, building of 2 plants in Belgium, operating **from 1980 until 1998** with an average production amounting to 50 tons  $U_3O_8$ /year
- **In 1981**, Prayon and Mechim succeeded in a industrial project of uranium extraction in Iraq on every stage to the start up in 1984
- **In 1998**, definitive stoppage of industrial activity in Belgium for Prayon and Puurs
- **Prayon : an indisputable and inescapable asset for project in Uranium recovery field**






# DEHPA/TOPO : Process Description

The Process consists in 4 steps or 4 sections :

- The pre-treatment of phosphoric acid
- The 1st cycle of extraction
- The 2<sup>nd</sup> cycle of extraction
- Precipitation and conditioning of yellow cake



# Flowsheet





## Pre-treatment of phosphoric acid

- Raw Phosphoric acid :
  - Is cooled and desaturated in agitated tank with suspended solids (up to 36 hours residential time)
  - Added with some adsorpting material (clay) to catch the organic matters
  - Added with flocculating material.
- Solids are separated by filtration or settling. Target : < 50 ppm solid
- Particular operations depending of acid quality
- Additional advantage : better quality of acid in downstream activities.



## 1<sup>st</sup> cycle of extraction

- Extraction and stripping made out of 3 or 4-stages battery of rectangular mixer-settler units
- For DEHPA/TOPO solvent :  $U^{+6}$  state for extraction and  $U^{+4}$  state for reductive stripping
- Use of scrap iron added to small flow of phosphoric strip acid to lower Redox potential = major factor for operation of the plant
- After extraction step and separation of solvent entrained, 1st raffinate (main flow of phosphoric acid) returns to the phosphoric acid production plant



## 2<sup>nd</sup> cycle of extraction

- Uranium oxidation :  $U^{+4} \rightarrow U^{+6}$  before extraction
- Filtration to catch iron phosphate
- Scrubbing to avoid any  $P_2O_5$  contamination in final YC
- Chemical reextraction : use ammonium carbonate solution to produce AUC
- Solvent acidification with sulfuric acid
- Solvent washing



# Precipitation and conditioning

## From AUC to yellow cake :

- Evaporation of AUC solution :
- $\text{AUC} \rightarrow \text{CO}_2\text{g} + \text{NH}_3\text{g} + \text{HAU}$  which precipitates
- Filtration
- Drying at  $120^\circ\text{C}$



## Site integration

### **Contemplated unit adjacent to existing plant of phosphoric acid plant**

#### Constraints :

- 1st cycle close to storage = location or lay out problems
- Activity of extraction uranium can't be no threat to objectives and/or long-lasting of phosphoric acid plant
- Industrial culture of supervisory and execution staff different to teach to the staff in charge of the new unit



## Site integration

**Contemplated unit adjacent to existing plant of phosphoric acid plant**

Assets :

- Equipments allocated to pre-treatment section
- Quality of phosphoric acid greatly improved thanks to pre-treatment and to the removal of uranium
- Staff with very good knowledge of phosphoric acid





## Prayon's experience : new risks

- Any phosphoric acid producer who invests in a unit of uranium extraction has to aware of new risks to manage :
  - Radioactivity contamination
  - Workers irradiation
- New activity to be done under control of National Approved Organisation : respect of regulatory or legal measures
- From 1980 to 1998, Prayon's staff of 2<sup>nd</sup> cycle of extraction zone was fitted with personal dosimeter, monthly read and analysed by the National Approved Organisation.
- During 18 years of operation and supervision, Prayon never had to move a worker away, neither for body contamination nor for irradiation. To reach that result, it is essential to integrate the management of risk from the design to the implement of a strict organisation of work during the operation.  
The risks linked to the use of organic solvent have to be managed as well.



# Prayon's experience : design

## General conception of 2ne cycle extraction unit

1. **Keep control on all outgoing flows and particularly to avoid leak of uranium in environment :**
  - containment wall for storage tanks
  - sump that enables pumping of eventual leak
  - slightly oblique floor towards gutters for part of the plant where extraction take place
  - isolation and placement under slight depression for part of the section containing the yellow cake.



# Prayon's experience : design

## General conception of 2ne cycle extraction unit

### 2. Keep all the working zones free of any contamination :

- wall and grounds made out or covered with non porous material
- finishing works of civil engineering to avoid location difficult to clean or decontaminate
- gutter covering with removable pieces made out of material resistant to acids and fuel and easily cleanable
- Section fitted with decontamination post



# Prayon's experience : design

## General conception of 2ne cycle extraction unit

### 3. Allow strict access control of this section :

- Access allowed from control room by security camera
- Two locker-rooms : a green changing-room (for civil clothes) and a red changing-room (for working clothes and protection equipment)

Between them :

- One « humid » locker-room with showers
- One « dry » locker-room to allowed access exit to potential visit and staff

Both locker-rooms fitted with Geiger counter



## Prayon's experience : Work Organisation

### Work organization strictly limited to authorized people

- Operating teams composed of
  - A process operator (chemist-technician)
  - A maintenance operator (electromechanical technician) able to internally repair small devices
- Visits of external people strictly limited
- Visitor will wear dosimeter. Date, name of the visitor and number of dosimeter noted in a visit book. At the exit, visitors will be checked with Geiger counter



## Prayon's experience : Decommissioning and decontamination

- If activity stopped, the site have to be decontaminated before dismantling and re-affectation of freed areas
- Decontamination is easier if principles followed during plant design phase
- Prayon had built its 2<sup>nd</sup> cycle of extraction in a 19th century building. Walls, 80 cm thick, were made up of extremely porous bricks => not a good choice.
- After the equipment decontamination by washing with sulphuric acid, decontamination required squaring 800 m<sup>2</sup> of walls. Each square was numbered and radioactivity had to be brought back to background level  
Locally, this required removal of 30 cm of the wall thickness to reach this level

















Thank you

**for your attention !**

---